



Allotment Sheds

Composited by Gareth Richards

September 2026

Allotment Shed Ideas and Storage

Allotment shed ideas for UK plots, covering local size rules, wall storage, seed care, fold-down benches, rainwater and security.



Allotment shed rules vary by landlord. Portsmouth permits structures up to 2.4m by 1.8m and 2.1m high, while Brighton permits 2m by 3m sheds up to 2.2m high. Check the tenancy before ordering. Use wall hooks, a fold-down bench and high shelves to preserve floor space. Take machinery home and secure hand tools out of sight.

Key takeaways

Check the tenancy agreement before buying because shed rules vary by site

Portsmouth permits 2.4m by 1.8m sheds, while Brighton permits 2m by 3m

Use wall hooks and high shelving to keep the floor clear for a wheelbarrow

A fold-down bench provides workspace without permanently blocking the aisle

Take machinery home and keep remaining tools hidden behind a stout lock

Good allotment shed ideas start with the site rules, then make every wall useful. Store tools vertically, keep seeds dry and leave enough floor space for safe access.

Rules are not standard across the UK. Portsmouth City Council permits sheds up to 2.4m by 1.8m and 2.1m high. Brighton & Hove City Council permits one 2m by 3m shed up to 2.2m high. Your own tenancy remains the deciding document.

What size shed can you have on an allotment?

Start with the landlord's written rules. Limits, permitted bases and consent processes differ between sites. Bristol City Council requires tenants to obtain Allotments Office permission before erecting or moving a shed. Manchester City Council also requires written consent for structures.

Treat 2.4m by 1.8m as one common example, not a national entitlement. Do not order materials until the site manager confirms the footprint, height, position and base.

Council example	Maximum footprint	Maximum height	Permission Note
Portsmouth	2.4m x 1.8m	2.1m	Contact the office for other structures
Brighton & Hove	2m x 3m	2.2m	One shed per plot
Bristol	Set by local approval	Set by local approval	Permission required before work

Position the shed where it will not shade neighbouring beds. Face the door towards a safe, level path. A guttered roof can feed a covered water butt if the tenancy permits one.

Keep the door clear of the main growing route. A firm, level approach reduces trips when carrying tools or compost. Our allotment path guide compares woodchip, gravel and slab routes for wet plots.

Fit gutters only after the site manager approves the structure. Route the downpipe into a covered water butt and secure the lid. The rainwater harvesting guide explains storage capacity, overflow and safe positioning. Do not let overflow discharge against the timber base.

Separate sharp tools from everyday hand tools. Wall clips work for spades and forks, while a closed box suits blades and fixings. Take a look at our winter tool-storage checklist before leaving equipment through the dampest months.

Choosing or building an allotment shed

You have three options: buy new, buy second-hand or build from reclaimed materials. Each has trade-offs, but every option needs consent, a sound base and a safe route from the site entrance.

Buying new gives you matching panels and instructions. Confirm where a delivery vehicle can stop, how panels will reach the plot and whether another person is available for lifting. Check that the supplied footprint and ridge height fit the written site rule.

Buying second-hand can reuse a sound structure, but inspect it before agreeing to dismantle it. Pay particular attention to the base rails, floor edges, lower door frame, roofing material and any blackened or soft timber. Label panels and fixings during dismantling so the shed can be rebuilt in the same order.

Building from reclaimed materials gives flexibility but does not remove the need for consent. Avoid treated timber of unknown origin where it could contaminate soil, and remove protruding nails or sharp edges before materials enter a shared allotment path.



Wall-mounted racks keep every tool visible and accessible, no more rummaging through piles

How to organise tools in an allotment shed

Tool organisation is the single biggest improvement you can make. Wall-mounted storage keeps handles separated and leaves a clear route through the shed. Choose a system that can support each tool securely.

Pegboard

Mount pegboard on spacer battens so hooks can slot in properly. It suits hand trowels, secateurs, dibbers, twine and labels. Keep packeted seed in a closed container rather than on an exposed board, and rearrange hooks as the tool collection changes.

Wall-mounted tool racks

Wooden or metal racks with spring-grip clips hold spades, forks, rakes, hoes and edging shears vertically. Mount each rack into sound framing rather than thin cladding. Place heavy tools low enough to remove without stretching, and test that no handle blocks the doorway.

Magnetic strips

A magnetic strip can hold small metal tools, but exposed blades do not belong at child height. Use a closed, labelled box for knives and sharp fixings. Wipe soil from tools before storage so moisture is not held against the metal.

Ceiling hooks

Fix suitable hooks into sound framing for light seasonal items such as netting, fleece rolls and an empty hose. Do not suspend heavy tools above a walkway or rely on hooks fixed only into thin roof boards.

Seed storage that actually preserves viability

Seeds last longest when they remain dry, cool and dark. A damp packet can develop mould or lose germination quality before the next sowing season.

Fold or clip each dry packet, then place it inside a labelled airtight container. Record the variety and packing or purchase year so older seed can be used first. A reusable desiccant sachet can help only when the seed and container are already dry; replace or recharge it according to its instructions.

Storage risk	Practical response
Open packet	Close it and move it into a labelled airtight container
Damp shelf	Find the leak and move seed away until the timber is dry
Direct sun	Use an opaque box in the coolest shaded part of the shed
Valuable or seed	Store it at home where temperature and moisture are steadier

Temperature matters. A shed can become hot in summer and damp in winter. Take valuable seed home if the building has wide temperature swings or leaks.

Setting up a potting bench in a small shed

A potting bench improves an allotment shed from pure storage into a functional workspace. You can prick out seedlings, pot up plants, mix compost, and label trays without bending over on the ground.



A fold-down bench and labelled seed jars create a proper propagation station in a small shed

Fold-down bench (best for 6x4ft sheds)

Mount a plywood or solid-timber worktop on brackets rated for the expected load. Set it at a comfortable working height, round exposed corners and add a positive catch so the surface cannot drop unexpectedly. Fold it away after use to restore a clear route through the shed.

Fixed bench (8x6ft sheds and larger)

A permanent bench along an end wall gives you a dedicated potting station. Add a raised back edge to contain loose compost and mount shallow shelving above for trays and labels. Keep a lidded bin beneath for waste, and make sure the remaining aisle is wide enough for safe entry and exit.

Essential bench equipment: a potting scoop, sieve for compost, dibber, waterproof labels, a permanent marker, and a bucket of clean water. Store these within arm's reach of the bench surface.

Allotment shed security

Allotment theft is a persistent problem across the UK. Power tools, copper piping, and quality hand tools are the most targeted items. Visible security helps, but no allotment shed is a safe place for valuable machinery.

Lock: Fit the hasp and hinges with coach bolts. Use a closed-shackle padlock and keep tools out of sight. Bristol City Council's allotment guidance gives the same advice and recommends taking expensive machinery home.

Tool marking: Mark hand tools with a plot identifier that does not disclose a home address. Keep serial numbers and photographs of distinctive equipment at home. This helps identify property without adding personal information to an unattended shed.

Don't store valuables. Leave battery packs, power tools, and anything expensive at home. The allotment shed should contain replaceable hand tools and consumables only. If you must leave a strimmer or mower on site, chain it to a ground anchor inside the shed.



A closed-shackle padlock reduces exposed metal, while coach bolts secure the hasp from inside

Lean-to extensions and covered areas



A lean-to extension adds dry storage for bulky items without increasing the shed footprint

A lean-to roof attached to one side of the shed can shelter a wheelbarrow, cane bundle or cold frame without using internal floor space.

Treat a lean-to as an additional structure, not as a loophole in the shed limit. Ask whether it needs separate consent and whether its footprint, drainage or shading would affect a neighbouring plot. Use a qualified installer when the framing, fixings or roof loading are outside your experience.

Essential allotment shed equipment checklist

This checklist covers the tools and supplies every allotment shed should contain. Tick off what you have and fill the gaps.

Item	Purpose	Storage position
Spade and fork	Digging and turning compost	Secure vertical rack
Hand trowel and fork	Planting and weeding	Pegboard or closed tray
Hoe and rake	Weed control and soil levelling	Secure vertical rack
Secateurs	Pruning and harvesting	Closed, dry box
Watering can	Targeted watering	Floor edge away from doorway
Wheelbarrow	Moving compost, soil and harvests	Clear bay or approved shelter
Twine and labels	Plant support and identification	Labelled drawer or box

Item	Purpose	Storage position
Seed trays and pots	Propagation	Nested on a high shelf
Fleece and netting	Frost and pest protection	Dry hooks away from blades
Timber treatment	Shed maintenance	Sealed container taken home if required
Padlock and spare key	record	Security Lock fitted outside; record kept at home

Buy only the tools the plot work requires. Reuse sound second-hand equipment where practical, inspect wooden handles and metal joints, and avoid filling the shed before there is a defined storage position for each item.

Shed maintenance through the seasons

Timber sheds on allotments face wind, rain and frost. A short inspection in dry weather can catch a leaking roof or wet base before stored tools are damaged.

During a dry spell in spring or early summer:

Treat external timber with a product suitable for the shed and allowed by the tenancy. Follow the manufacturer's preparation, temperature and drying instructions.

Pay extra attention to the base rail, door frame, and end grain where moisture enters first.

Check roofing felt for tears or lifted edges. Re-nail or patch with bitumen adhesive.

Clear soil, leaves, and debris from the base perimeter. Organic material banked against the base rail traps moisture and accelerates rot.

Every autumn (October):

Tighten loose screws and re-nail any sprung boards.

Oil door hinges and the padlock mechanism.

Check the floor for soft spots, probe with a screwdriver. Soft timber means rot has started.

Ensure the water butt is draining properly and not overflowing against the shed wall.

Record repairs and the treatment product used. If the base, floor or framing becomes soft, stop loading that area and repair it before relying on the structure again.

Frequently asked questions

What size shed am I allowed on an allotment?

Allotment shed limits depend on the landlord and site rules.

Portsmouth permits 2.4m by 1.8m sheds, while Brighton permits 2m by 3m.

Do I need permission for an allotment shed?

Check your tenancy before buying or building any structure.

Bristol requires Allotments Office permission, while Manchester requires written consent for sheds and greenhouses.

How do I secure an allotment shed?

Use coach bolts and a closed-shackle padlock. Take machinery home, keep tools out of sight and report theft to the police and site manager.

What is the best way to store seeds in a shed?

Keep dry seed packets inside labelled airtight containers. Put them in the coolest, darkest cupboard and take valuable or temperature-sensitive seed home.

How do I organise tools in a small allotment shed?

Hang long tools vertically and keep the floor clear. Use pegboard for hand tools, a high shelf for seasonal kit and hooks for netting.

How to Contact the Editor

If you have comments or you know I have given wrong advice then please contact me by email at

info@yeovil-allotments-association.co.uk

If you have something to contribute or have a say on allotment life, then please use my email to send your contributions.

I am going to process the magazine issue once a month, so if there are comments you would like to make they can be answered in future editions.

I would like to add that most of the articles are taken off the web and some well known gardening and allotments magazines have been read in the making of our magazine content.

We also have our own website at :

www.yeovil-allotments-association.co.uk


where you can find this magazine as well as a catalogue

Happy Allotmenting and best wishes,

Gareth Richards

Treasurer

Eliz Flats, Plot 14



Editor : Gareth Richards – Treasurer

Yeovil Allotments Association

Website :

www.yeovil-allotments-association.co.uk

Email :

info@yeovil-allotments-association.co.uk

gareth.richards@yeovil-allotments-association.co.uk